

FEB 02 2009

Application Serial No. 10/591,020  
Reply to office action of November 6, 2008

PATENT  
Docket: CU-5023

### Amendments To The Claims

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

#### Listing of claims:

1. (currently amended) A method for negotiating bandwidth of a Data Communication Channel (DCC) automatically, comprising the steps of:
  - performing a first communication channel configuration by two network elements respectively;
  - informing, by the network element at transmitting end of the DCC, the network element at receiving end of the DCC of a DCC negotiation message via the ~~preconfigured communication channel~~ DCC;
  - after receiving the DCC negotiation message, the network element at the receiving end comparing ~~the~~ overhead bytes contained in the DCC negotiation message with overhead bytes available to the network element at the receiving end, to obtain an intersection, which ~~is~~ are overhead bytes, for constructing a DCC, available to both the network elements, wherein the overhead bytes as bandwidth of the ~~channel~~ DCC are used to perform a second DCC configuration in the same order, so as to establish the DCC.
2. (previously presented) The method according to claim 1, comprising:
  - sending a DCC connection command from the two network elements to the opposite network element via the newly-configured DCC respectively;

Application Serial No. 10/591,020  
Reply to office action of November 6, 2008

PATENT  
Docket: CU-5023

after receiving the DCC connection command, sending a DCC connection acknowledgement command from the two network elements to the opposite network element respectively;

accomplishing establishment of the DCC after the two network elements receive the DCC connection acknowledgement commands.

3. (original) The method according to claim 1, wherein the first communication channel configuration is performed in default configuration mode.
4. (original) The method according to claim 1, wherein each DCC of the network elements determines whether to perform the DCC bandwidth negotiation in accordance with the requirements of users.
5. (original) The method according to claim 3, wherein the network elements return to the default DCC configuration state if the configured timer is expired at any step during the second DCC establishment process.
6. (original) The method according to claim 3, wherein both of the network elements at the transmitting and receiving ends of the DCC return to the default DCC configuration state if the preconfigured connected DCCs fails.
7. (original) The method according to claim 3, wherein both of the two network elements perform the first DCC configuration by using one or more unused overhead

Application Serial No. 10/591,020  
Reply to office action of November 6, 2008

PATENT  
Docket: CU-5023

bytes in a section overhead, the one or more unused overhead bytes in the section overhead comprising: D bytes and other unused section overhead bytes.

8. (original) The method according to claim 1, wherein the DCC negotiation message comprises: overhead bytes and the order of the overhead bytes available to the transmitting end of DCC of the current network element.
9. (original) The method according to claim 7, wherein the D bytes are in an order from D1 to D12.
10. (original) The method according to claim 3, wherein during the second DCC configuration, the default DCC constructed by the default section overhead bytes is reserved, and the new DCC is constructed by using the newly-added section overhead bytes.
11. (original) The method according to claim 1, wherein the SDH/SONET section overhead bytes for constructing the DCC are overhead bytes selected from a group consisting of D1-D12 bytes and other unused section overhead bytes, wherein the section overhead bytes used in the network elements at both ends of the DCC are consistent with each other.